

Europäisches Patentamt

European Patent Office

Office européen des brevets



(11) EP 0 865 041 A2

(12) EUROPEAN PATENT APPLICATION

(43) Date of publication:
16.09.1998 Bulletin 1998/38

(51) Int. Cl.⁶: G11B 20/18

(21) Application number: 98103412.7

(22) Date of filing: 27.02.1998

(84) Designated Contracting States:
AT BE CH DE DK ES FI FR GB GR IE IT LI LU MC
NL PT SE
Designated Extension States:
AL LT LV MK RO SI

(72) Inventor: Hütter, Ingo
29223 Celle (DE)

(30) Priority: 12.03.1997 DE 19710022


(74) Representative:
Hartnack, Wolfgang, Dipl.-Ing.
Deutsche Thomson-Brandt GmbH
Licensing & Intellectual Property,
Göttinger Chaussee 76
30453 Hannover (DE)

(71) Applicant:
DEUTSCHE THOMSON-BRANDT GMBH
78048 Villingen-Schwenningen (DE)

(54) Method and apparatus for the processing and outputting of data

(57) In a further development of the CD, the so-called DVD, a data format was chosen which is upwards compatible with the CD. As a result, existing audio CDs can also be played on a DVD player. If complete error correction is not possible during the reproduction of a CD by an audio CD player, then simple measures for error concealment are additionally taken, but they are not always adequate. However, for cost reasons more complicated methods are not used in an audio CD player, since they would require a more powerful processor and a larger memory. However, a DVD player has

this more complex hardware in any event, in order to enable the outstanding video quality that is intended. According to the invention, therefore, during the reproduction of an audio CD on a DVD player, one of various error concealment methods is carried out in dependence on the error rate that occurs, with a low error rate it being possible to effect error concealment that is considerably more accurate in comparison with a conventional CD player.



EP 0 865 041 A2

Description

The invention relates to a method and an apparatus for the processing and outputting of data which are stored on a data medium, in particular a method and an apparatus for error concealment during the reproduction of audio CDs.

Background

At present, a further development of the CD, the so-called DVD ("Digital Video Disc" or "Digital Versatile Disc"), is about to be introduced on the market. The DVD is likewise an optical data medium having the same dimensions as those of the CD, but a considerably higher data storage capacity than the CD. The players for DVDs will in some instances also enable the playing of existing audio CDs.

During the reproduction of a compact disc (CD) by an audio CD player, the EFM (eight-to-fourteen modulation) signal is obtained from the optically scanned signal after pulse shaping. After EFM demodulation, the signal obtained in this way is firstly fed to an error correction circuit prior to outputting by a digital-to-analogue converter. In the error correction circuit, coding of the data at the recording end in accordance with the cross-interleave Reed-Solomon method is reversed. For this purpose, the signal is read into a memory and is read out again in the de-interleaved order. If complete error correction is not possible, then measures for error concealment are additionally taken in order to reduce the audibility of these errors. These error concealment methods implemented in an audio CD player are simple and not always adequate. However, more complicated methods are not used for cost reasons, since they would require a more powerful processor and a larger memory. If the data loss is very great, only the muting of the signal therefore remains in the extreme case.

Invention

The invention is based on the object of specifying a method for improved error concealment during the reproduction of data, the data being read from a data medium, in particular from a CD or a DVD. This object is achieved by means of the method specified in claim 1.

The invention is based on the further object of specifying an apparatus for application of the method according to the invention. This object is achieved by means of the apparatus specified in claim 6.

Compared with a conventional CD player, a DVD player has a considerably more powerful processor and a significantly larger buffer memory. This more complex hardware is necessary in order to enable the outstanding video quality that is intended. When a CD is played by a DVD player, therefore, the audio data that are read can be buffer-stored in the buffer memory, and processed, to a greater extent in order e.g. to perform error

concealment. This error concealment can be carried out considerably more accurately than with a conventional CD player, since more complex algorithms can be processed by the more powerful processor. This does presuppose, however, that high-quality CDs are used and the DVD player is installed at an undisturbed location. By contrast, poor-quality CDs require error concealment to be carried out more frequently, with the result that it is then no longer possible to use a complex error concealment method. Likewise, in the event of frequent vibrations and/or with portable devices, the pick-up is often required to effect a return, with the result that it is likewise not possible to carry out complex error concealment in this case.

In principle, the inventive method for the processing and outputting of data which are read from a data medium and buffer-stored consists in selecting one of various processing methods in dependence on the number of buffer-stored data.

In this case, the number of buffer-stored data may depend in particular on the error rate of these data.

In this case, the data are preferably read from the data medium at a first rate and, following buffer-storage and processing, are output at a second rate.

In an advantageous manner, error concealment methods of different complexity are carried out in the various processing methods, which error concealment methods serve to reduce data errors which could not be eliminated earlier on by error correction.

In a particularly advantageous manner, the method can be employed when the data are optically read from the data medium, the data being audio signals.

In principle, the inventive apparatus for the processing and outputting of data which are read from a data medium comprises means for reading data media, one or more memories for buffer-storing the data, and also means for processing the data and means for switching between various processing methods in dependence on the occupancy of the memory or of the memories.

It is advantageous here if the means for processing the data can carry out error concealment methods of different complexity for the purpose of reducing data errors.

The means for reading data media are preferably suitable for data media having different data formats.

In this case, an expedient refinement of the concept of the invention envisages that the apparatus is suitable for the reproduction of audio CDs and DVDs, and is part of a DVD player or of a DVD-ROM drive, which may in turn be configured as a separate device or be integrated in another device.

Drawing

An exemplary embodiment of the invention is described with reference to Fig. 1. The latter shows a block diagram of a DVD player according to the invention.

Exemplary embodiments

Fig. 1 illustrates a DVD device according to the invention. First of all the information stored on the CD disk is read by an optical scanning system which is part of the pick-up P. The optical scanning system is in this case able to read both CD disks and DVD disks. The signal obtained is then subjected to pulse shaping and EFM demodulation, after which it is fed to an error correction circuit. This part of the signal recovery is also still part of the entire pick-up P. The data are then read into a first buffer memory M1, this being carried out at a higher rate than in the case of a conventional CD player, e.g. at a doubled rate. A continuity check CC then follows, in which the continuity in the data stream is checked. If there is no continuity in the data stream or the buffer memory M1 is filled by the high reading rate, a return in the pick-up is compelled. This is then followed, after further buffer-storage in the buffer memory M2, by the actual error concealment EC. Afterwards, the data are then output via a D/A converter DA. The quality and hence the complexity of the error concealment chosen is in this case chosen in dependence on the occupancy of the buffer memory M3 and/or of the error rate that occurs. If this memory is well filled, it is possible to use error concealment strategies that require more time, in particular more extensive interpolation algorithms.

The three buffer memories M1, M2 and M3 may be arranged in the same RAM, in which case only the size of the three buffer memories changes dynamically. The data are stored in data sectors, in which case a data sector is released for renewed writing when the content of this data sector has been output by the D/A converter DA, or a data sector is released by the continuity check CC. The arrows in Fig. 1 symbolize the transport path for the data sectors. In this case, the data are not actually forwarded between the processes, rather only pointers to the data are altered.

Since the processor of a DVD player is not utilized to capacity during the reproduction of an audio CD, all the data blocks will normally accumulate upstream of the output process, since its speed does not depend on the processor power but on the output data rate.

The excess processor power can therefore be utilized for error concealment, without additional hardware being necessary and thus higher costs being entailed. In this case, erroneous samples can be concealed e.g. by complex interpolation using previous and succeeding error-free samples. If the queue between error concealment EC and the actual output process DA is very long, it is possible to perform a good and correspondingly time-consuming error concealment. If the queue has then shrunk to below a specific length, however, a switch is made back to a simpler concealment. Consequently, given the use of high-quality CDs and an undisturbed location where the CD player is installed - and thus only very seldom occurring non-correctable errors

- it is always possible to use the best method for error concealment and thus achieve a better reproduction quality than with a conventional CD player. If, on the other hand, the CD is of a very poor quality or difficult reproduction conditions prevail, then error concealment would have to be carried out very frequently. In this case, it would then no longer be possible to employ a very complex method for error concealment, rather a simpler error concealment method ensuring at least a minimum quality would be used.

It is also possible to utilize the excess processor power and/or the memory of a further, external device for the method according to the invention. The external device may in this case be e.g. a television set or a set-top box. However, it is equally possible to connect the CD or DVD player to a computer or integrate it therein.

The invention can be utilized for the reproduction of digital audio signals. These will be signals in the PCM format, in particular. In the PCM method, at intervals defined by the sampling rate, the respectively current value of the audio curve is determined and stored in numerical form, a specific number of bits (usually between 8 and 24) being combined each time. It is possible to effect reproduction both of audio CDs by a CD player or DVD player and of DVDs with PCM audio data on a DVD player. An application for the audio reproduction of minidisks is also conceivable.

However, the invention is in no way restricted to the read-out, processing and reproduction of audio signals. Rather it is equally possible to process and/or correct data errors in video data or other data. Therefore, an application in the reproduction of Video-CDs, Photo-CDs, CD-ROMs, personally recorded CD-Rs or other optically readable data media on a DVD player or other future further developments is also conceivable.

Claims

1. Method for the processing and outputting of data which are read from a data medium and buffer-stored, characterized in that one of various processing methods is selected in dependence on the number of buffer-stored data.
2. Method according to claim 1, wherein the number of buffer-stored data depends on the error rate of these data.
3. Method according to claim 1 or 2, wherein the data are read from the data medium at a first rate and, following buffer-storage and processing, are output at a second rate.
4. Method according to one of the preceding claims, wherein error concealment methods of different complexity are carried out in the various processing methods, the error concealment methods serving to reduce data errors which could not be eliminated

earlier on by error correction.

5. Method according to one of the preceding claims, wherein the data are read optically from the data medium, the data being audio signals. 5
6. Apparatus for the processing and outputting of data, having means (P) for reading a data medium, one or more memories (M1, M2, M3) for buffer-storing the data read out, and means for processing (EC) the data, characterized in that means for switching between various processing methods in dependence on the occupancy of the memory or of the memories are furthermore provided. 10 15
7. Apparatus according to claim 6, wherein the means for processing (EC) the data can carry out error concealment methods of different complexity for the purpose of reducing data errors. 20
8. Apparatus according to claim 7, wherein the means (P) for reading data media are suitable for data media having different data formats.
9. Apparatus according to claim 8, wherein the means (P) for reading data media enable reproduction of audio CDs and DVDs, and are part of a DVD player or of a DVD-ROM drive, it being possible for the DVD player or the DVD-ROM drive in turn to be configured as a separate device or to be integrated in another device. 25 30 35 40 45 50 55





FIG. 1



Europäisches Patentamt
European Patent Office
Office européen des brevets



(11) EP 0 865 041 A3

(12) EUROPEAN PATENT APPLICATION

(88) Date of publication A3:
09.12.1998 Bulletin 1998/50

(51) Int. Cl.⁶: G11B 20/18

(43) Date of publication A2:
16.09.1998 Bulletin 1998/38

(21) Application number: 98103412.7

(22) Date of filing: 27.02.1998

(84) Designated Contracting States:
AT BE CH DE DK ES FI FR GB GR IE IT LI LU MC
NL PT SE
Designated Extension States:
AL LT LV MK RO SI

(72) Inventor: Hütter, Ingo
29223 Celle (DE)

(30) Priority: 12.03.1997 DE 19710022


(74) Representative:
Hartnack, Wolfgang, Dipl.-Ing.
Deutsche Thomson-Brandt GmbH
Licensing & Intellectual Property,
Göttinger Chaussee 76
30453 Hannover (DE)

(71) Applicant:
DEUTSCHE THOMSON-BRANDT GMBH
78048 Villingen-Schwenningen (DE)

(54) Method and apparatus for the processing and outputting of data

(57) In a further development of the CD, the so-called DVD, a data format was chosen which is upwards compatible with the CD. As a result, existing audio CDs can also be played on a DVD player. If complete error correction is not possible during the reproduction of a CD by an audio CD player, then simple measures for error concealment are additionally taken, but they are not always adequate. However, for cost reasons more complicated methods are not used in an audio CD player, since they would require a more powerful processor and a larger memory. However, a DVD player has

this more complex hardware in any event, in order to enable the outstanding video quality that is intended. According to the invention, therefore, during the reproduction of an audio CD on a DVD player, one of various error concealment methods is carried out in dependence on the error rate that occurs, with a low error rate it being possible to effect error concealment that is considerably more accurate in comparison with a conventional CD player.



EP 0 865 041 A3



European Patent
Office

EUROPEAN SEARCH REPORT

Application Number
EP 98 10 3412

DOCUMENTS CONSIDERED TO BE RELEVANT			
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (Int.Cl.6)
X Y	EP 0 578 124 A (SONY CORP) 12 January 1994 * figures 2,3,5 * * abstract * * column 1, line 11 - line 20 * * column 5, line 31 - line 57 * * column 6, line 1 - line 53 * * column 7, line 26 - line 44 * ----	1,3,5,6 2,7	G11B20/18
A Y	US 4 665 513 A (WENGLER ROLF) 12 May 1987 * column 1, line 6 - line 13 * * figures 1,2 * * claims 1,10 * * column 2, line 58 - line 61 * * column 3, line 16 - line 37 * * column 4, line 19 - line 68 * * column 5, line 1 - line 28 * * column 6, line 3 - line 12 * ----	1,4-6 2,7	
A	EP 0 742 552 A (SANYO ELECTRIC CO) 13 November 1996 * abstract * * table 4 * * page 2, line 20 - line 28 * * page 2, line 34 - line 45 * * page 3, line 3 - line 8 * ----	8,9	TECHNICAL FIELDS SEARCHED (Int.Cl.6) G11B
A	DE 296 19 764 U (REGER GERD ; REHM WALTER (DE); SCHILLER BERND (DE)) 16 January 1997 * the whole document * -----	8,9	
The present search report has been drawn up for all claims			
Place of search THE HAGUE		Date of completion of the search 12 October 1998	Examiner Barel-Faucheux, C
<p>CATEGORY OF CITED DOCUMENTS</p> <p>X : particularly relevant if taken alone Y : particularly relevant if combined with another document of the same category A : technological background O : non-written disclosure P : intermediate document</p> <p>T : theory or principle underlying the invention E : earlier patent document, but published on, or after the filing date D : document cited in the application L : document cited for other reasons ----- & : member of the same patent family, corresponding document</p>			

EPO FORM 1503 03/82 (P04C01)